NewTechWood
INTERIORS

Hybrid Plus+
FLOORING

Thailand Distributor, K.S. WOOD Co., Ltd. | www.kswood.com

Scratch Resistance

Termite Protection

Water Resistance

NewTechWood INTERIORS | Hybrid Plus+ FLOORING


Scratch Resistance
Termite Protection
Water Resistance
NewTechWood
INTERIORS
Hybrid Plus+
FLOORING

SONY

Scratch Resistance

Termite Protection

Water Resistance

NewTechWood INTERIORS | Hybrid Plus+ FLOORING

Locking systems to last a lifetime

Best installation system



Upgrade with exclusive features

Fold down

5G

Licensed by Välinge

3x Faster	installation
Easiest	click system
50% stronger	locking
Large tolerance	window

STRONG LOCKING

หมดปัญหาหัวไม้ห่าง

NO LEAK, NO WORRIES
น้ำไม่ซึมระหว่างรอยต่อ

FAST & EASY INSTALL
ติดตั้งง่ายและรวดเร็ว



5G – profile example

Licensed by Välinge

- ติดตั้งง่าย รวดเร็ว และแข็งแกร่งที่สุด
- จับลิ้นไม้เข้าหากันแล้วพับลง ล็อกลิ้นไม้ทันที
- ล็อกไม้สนิท ไม่เลื่อนขยับขณะเดิน

● รองรับการติดตั้งพื้นหลากหลายแพทเทิร์น ทั้งลายก่ออิฐ แรนดอม

NewTechWood INTERIORS | Hybrid Plus+ FLOORING

LAYERS



LAYERS

UV Coating Plus+

High Density Wear Resistant Layer+
Thickness: 0.5 mm

Decor Film High Resolution+

2G Click System

Stone Composite Premium Grade+
Thickness: 5.5 mm

5G Click System+

IXPE Underlayment
Thickness: 1 mm

Total Thickness: 7 mm

Pet Friendly

บอกลารอยขีดข่วน และขจัดคราบสกปรกได้ง่ายดาย
ด้วยพื้นที่ออกแบบมารองรับสัตว์เลี้ยงโดยเฉพาะ

Easy Installation

การติดตั้งแบบ No-gap (ไม่มีช่องว่าง)
ช่วยลดฝุ่นขณะติดตั้ง และยังติดตั้งง่ายอีกด้วย

Low Maintenance

พื้นผิวทำความสะอาดง่าย ใช้เวลาไม่นาน

ช่วยให้คุณมีเวลาสบายๆ มากขึ้น

Indoor Use

เหมาะสำหรับใช้งานภายใน ได้แก่
ห้องครัว ห้องซักรีด หรือห้องอเนกประสงค์

Durable Materials

มีความทนทานต่อรอยขีดข่วน แรงกระแทก
และความเสียหายที่เกิดจากการใช้งานในชีวิตประจำวัน

Multiple Color Options

มีสีให้เลือกมากมาย หลากหลายสไตล์

ที่ลงตัวกับสไตล์อันเป็นเอกลักษณ์ของคุณ

ไม้พื้น Hybrid Plus+ Flooring พลัสคุณสมบัติพิเศษ ครบครันสำหรับงานพื้นไม้ภายใน ด้วยโครงสร้างแข็งแกร่งและทนชื้น 100%

- ลายไม้สวยเป็นธรรมชาติด้วยเทคโนโลยี EIR พร้อมคลือบผิวหน้ากันรอยขีดข่วนด้วย UV Coating ถึง 7 ชั้น จากผลิตภัณฑ์สีของ Treffert จากประเทศ Germany
- ชั้น Wear Layer หนาถึง 0.5 mm. มากกว่าทั่วไปถึง 2 เท่า
- แผ่นไม้มีความหนารวม 7 mm. ให้ความรู้สึกแน่นเท้าเวลาเดิน
- โครงสร้าง Core Board ผลิตจากวัสดุ Stone Composite ใหม่ 100% (Vergin Material Grade) แข็งแรงทนทานใช้งานได้นาน
- ติดตั้งได้ทุกชั้น หมดกังวลเรื่องความชื้น
- ระบบลิ้นล็อก แบบ 2G และพิเศษ 5G Click System
- รองด้วยแผ่นซับรองรับการกระแทกจากการใช้งาน วัสดุ IXPE พื้นแน่น หมดปัญหาเสียงรบกวน
- ปลอดภัยยิ่งขึ้น ด้วยค่ากันความลื่นระดับ R10 (Slip Resistance) ช่วยป้องกันการลื่นล้ม
- Pet Friendly เป็นมิตรต่อสัตว์เลี้ยงและอุ้งเท้าแมวและสุนัข

NewTechWood INTERIORS | Hybrid Plus+ FLOORING

CERTIFICATE

EUROPEAN STANDARD

Water Proof

Slip Resistance

Effect of Castor Chair

Scratch Resistance

Chemical Resistance

Colour Fastness

Reaction to Fire

NewTechWood
INTERIORS

Hybrid Plus+
FLOORING

PRODUCT CATALOG

Thailand Distributor, K.S. WOOD Co., Ltd. | www.kswood.com

Hybrid Plus+ FLOORING

Scratch Resistance
Termite Protection
Water Resistance

HBP01

Portland Warm Beige

PRODUCT INFORMATION

Code	HBP01
Stone Composite	5.5 mm.
Wear Layer	0.5 mm.
Backing IXPE	1 mm.
Size	7x180x1220 mm.
Finish	UV Coating EIR (Embossed in Register)

Licensed by Välinge



5G – profile example

5G Licensed by Välinge

NewTechWood INTERIORS | Hybrid Plus+ FLOORING

Scratch Resistance

Termite Protection

Water Resistance

HBP02

Memphis Middle Brown

PRODUCT INFORMATION

Code	HBP02
Stone Composite	5.5 mm.
Wear Layer	0.5 mm.
Backing IXPE	1 mm.
Size	7x180x1220 mm.
Finish	UV Coating EIR (Embossed in Register)

Licensed by Välinge



5G – profile example

5G Licensed by Välinge

NewTechWood INTERIORS | Hybrid Plus+ FLOORING

Hybrid Plus+
FLOORING



Scratch Resistance

Termite Protection

Water Resistance

HBP03

Highland Park Dark Brown

PRODUCT INFORMATION

Code	HBP03
Stone Composite	5.5 mm.
Wear Layer	0.5 mm.
Backing IXPE	1 mm.
Size	7x180x1220 mm.
Finish	UV Coating EIR (Embossed in Register)

Licensed by Välinge



5G – profile example

5G Licensed by Välinge

NewTechWood INTERIORS | Hybrid Plus+ FLOORING

STANDARDS & SPECIFICATIONS

Subject	Parameter Value	Reference Standard
Squareness	≤0.15 mm	ISO24342
Straightness	≤0.15 mm	ISO24342
Overall Thickness	± 0.20 mm	ISO24346
Wear Layer Thickness	± 0.03 mm	ISO24340
Surface Treatment	UV Coating	
Dimensional Stability (6hrs at 80°C)	<0.10 %	ISO23999
Curling (6hrs at 80°C)	≤1.2 mm	ISO23999
Density	≤1.9 g/cm^{3}	ISO23997
Residual Indentation	≤0.10 mm	ISO24343-1
Residual Indentation	≤8%	ASTM-1914
Ply Adhesion (film + Back pad)	≥60N/50mm	ISO10582
Locking Strength of click joint	>120N/50mm	EN 16511
Vertical buckle strength	>120N/40mm	In House
Effect of caster Chair (with pad)	15000	ISO 4918
Effect of caster Chair (without pad)	25000	ISO 4918
Gaps between tiles	≤0.10 mm	EN 16511
Height difference between tiles	≤0.10 mm	EN 16511
Abrasion Resistance	Class: AC4	EN 13329 /E
Abrasion Resistance	Group T	EN 660-2
Scratch Resistance	≥9N	Scleromer
Micro-scratch resistance	≤MSR-A2 / B1	EN 16094
Thermal expansion	<0.15% (10-45°C)	In House
Reaction to Fire	Bfl-s1	EN 13501-1
Electric Resistance	Body Voltage≤2.0KV	EN 1815
Electric Antistatic resistance	Antistatic	EN 1815
Staining and resistance to chemicals	Class 0	ISO26987
Flatness of tiles—Cuping fw, Convex	≤0.15%	EN 16511
Flatness of tiles—Cuping fw, Concave	≤0.10%	EN 16511
Flatness of tiles—Cuping fi, Convex	≤0.5%	EN 16511
Flatness of tiles—Cuping fi, Concave	≤0.25%	EN 16511

Resistance to Staining	Rating 5 no change	BS EN 438 (Group 1
Air Comfort	PASS	
Floor Score	PASS	
French VOC label	A+	
Acoustic	ΔLw≥19db	ISO 10140
Color Fastness	≥6 Δ ≤8	ISO 105
TVOC	≤0.5mg/m^3	CDPH/EHLB Standard
Slip Resistance	Wet 35 R10 DS	BS 7976 Din 51130 EN 13893
Toxicity	Not Toxic	EN 71
Formaldehyde	E0	EN 717
Only Virgin Material used?	YES	

NewTechWood
INTERIORS

Hybrid Plus+
FLOORING

ACCESSORIES

Thailand Distributor, K.S. WOOD Co., Ltd. | www.kswood.com

FLOOR CORNICE

Code:	B05,B07,B09
Construction:	PVC
Size:	13x50x2400 mm.
Color:	
Cutting Details:	

Hybrid Plus+
FLOORING
ACCESSORIES

JOINT

Code	AJ02,AJ06,AJ17
Construction	PVC
Size	8x50x2400 mm.
COLOR:	
Cutting Details	

Hybrid Plus+
FLOORING
ACCESSORIES

EDGING

Code	AE01,AE02,AE04
Construction	PVC
Size	8x50x2400 mm.
COLOR:	

Cutting Details



Hybrid Plus+
FLOORING
ACCESSORIES

STAIR NOSING

Code:	AS07,AS13,AS16
Construction:	PVC
Size:	20x60x2400 mm.
Color:	

Cutting Details:



Hybrid Plus+
FLOORING
ACCESSORIES



สัมผัส

รรรมชาติ

ได้ ในบ้านคุณ

Line Official Account

+669 5878 6710

www.kswood.com

Thailand Distributor, K.S. WOOD Co., Ltd.

wood
สัมผัส
ธรรมชาติ
ได้ในบ้านคุณ